



Oasis Shelters



Vented Gable Shelters- S30006

Our shade shelters are made with A500 Grade B Steel. Our three stage coating process includes sandblasting, zinc-rich primer base coat, and polyester powder coating.



Oasis Shelters

Tel: 1.905.766.2462

Web: www.OasisShelters.com

Email: info@OasisShelters.com

Address: 2400 Lucknow Drive, Unit 39, Mississauga, ON L5S 1T9, Canada

4


3

2

1

B

B





NOTES:

- 1- STRUCTURE:
HSS TUBES SHALL CONFORM TO ASTM A500, GRADE B
STEEL ANGLES SHALL CONFORM TO ASTM A36
STEEL PLATE SHALL CONFORM TO ASTM A36
- 2- HARDWARE:
BOLTS SHALL CONFORM TO ASTM A325 OR EQUIVALENT
NUTS SHALL CONFIRM TO ASTM A563 OR EQUIVALENT
- 3- STRUCTURE FINISH:
SAND BLASTED AND ZINC RICH PRIMER BASE COATED.
FINAL COAT: UV RESISTANT POLYESTER POWDER.
- 4- ROOF PANELS:
AGWAY PROFILE 7-150-NF - 24 GUAGE
CONFORMS TO ASTM A653 / CSA-S136-07
- 5- DESIGN SHOWN IS FOR REFERENCE PURPOSES ONLY,
SITE SPECIFIC DESIGN WILL BE PROVIDED
WITH ORDER.


A

A



MODEL NO	A [FT]	B [FT]	AI [FT]	BI [FT]	H [FT]	NO OF POSTS
S30006-16X24	16	24	2	2	9.5	6
S30006-20X30	20	30	2	2	9.5	6
S30006-30X40	30	40	2	2	9.5	8

Oasis
Shelters



ALL INFORMATION CONTAINED
IN THIS DOCUMENT IS PROPERTY
OF OASIS SHELTERS AND IT
MAY NOT BE REPRODUCED OR
COMMUNICATED WITHOUT
PERMISSION IN WRITING
FROM OASIS SHELTERS.

DATE
(yyyy.mm.dd)
2026.07.07

UNIT
INCH
[MM]

VENTED GABLE
SHADE STRUCTURE

SHEET

DRAWING NO

S30006-01-D15

REV


A

4


3

2


1



DETAIL A
SCALE 1:4



(8) - 15M VERTICALS
W/ 10M TIES @ 12" OC
2-10M TIES AT TOP
OF PIER



SECTION A-A

GEOTECHNICAL ENGINEER TO
CONFIRM SOILS ASSUMPTIONS:

1. RELIABLE COMPETENT SOILS ASSUMED
TO BE AT A DEPTH OF 1.5' BELOW TOP OF
GRADE. IF LOOSE SOIL LAYER EXTEND
DEEPER THAN 1.5', PIER IS REQUIRED
TO BE FOUNDED DEEPER, CONTACT
STRUCTURAL ENGINEER.
2. COHESIVE SOILS PROPERTIES:
A. MIN. DENSITY = 18 kN/M³
B. MIN. SHEAR STRENGTH = 25 kPa
3. COHESION-LESS SOILS PROPERTIES:
A. MIN. DENSITY = 18 kN/M³
B. ANGLE OF INTERNAL FRICTION = 18 Deg.

Oasis
Shelters

ALL INFORMATION CONTAINED
IN THIS DOCUMENT IS PROPERTY
OF OASIS SHELTERS AND IT
MAY NOT BE REPRODUCED OR
COMMUNICATED WITHOUT
PERMISSION IN WRITING
FROM OASIS SHELTERS.

DATE
(yyyy.mm.dd)

2026.07.07

UNIT

INCH
[mm]

SHEET

1/1

SHADE STRUCTURE
FOOTING DETAILS

DRAWING NO

S40001-01

REV

A